



UD TRUCKS

EURO 4



NEW
Kuzer
Made To Deliver Extra

Going the Extra Mile



Scan here to UD Trucks
Brochure Gallery

New Kuzer SKE155 Product Specifications

MODEL NAME		BPR75UKH	BQR75UKN
Axle Configuration		4x2	
Performance	GVW Rating (kg)	7,500	8,500
	Minimum Turning Radius (m)	7.1	
	Max Speed (km/h)	100km/h with Speed Limiter	90km/h with Speed Limiter
	Max. Gradeability (%)	31.3	31.0
Engine	Model	4HK1-TC	
	Emission Level	Euro 4	
	Type	4-Cylinder Inline, 4 Cycle, Water-Cooled, DOHC, VGS Turbo with Intercooler	
	Bore x Stroke (mm)	115 x 125	
	Engine Displacement (cc)	5,193	
	Max. Output	155PS @ 2,600rpm	
	Max. Torque	419 N.m @ 1,600 rpm - 2,600 rpm	
	Fuel System	Commonrail Direct Injection System	
Transmission	Model	MYY6S	
	Type	6-Speed Manual Transmission with Overdrive	
	Gear Shift	Mechanical, Cable Type Gear Shift Linkage	
	Clutch System	Pull Type with Dry Single Plate, Hydraulic Operated, Diameter 325mm	
Chassis	Front Axle	Reverse Elliot, I-Beam	
	Front Axle Designed Capacity (kg)	3,100	3,300
	Rear Axle	Full Floating with Single Reduction Hypoid Gearing	
	Rear Axle Designed Capacity (kg)	6,600	
	Final Gear Ratio	4.556	5.125
	Frame Width (mm)	850	
	Frame Dimension - Height x Width x Thickness (mm)	216 x 70 x 6	
	Front Suspension	Semi-Elliptical Alloy Steel Leaf-spring with Double Acting Telescopic Shock Absorber	
	Rear Suspension	Semi-Elliptical Alloy Steel Leaf-spring with Double Acting Telescopic Shock Absorber	
	Steering System	Hydraulic Power Assisted, Recirculating Ball Type	
	Service Brake (Foot Brake)	Drum brakes with Dual Circuit Hydraulic Control, Hydraulic Pressure Assistance, ABS with EBD	
	Parking Brake (Hand Brake)	Mechanical, Internal Expanding Acting on Transmission Output Shaft	
	Auxiliary Brake	Vacuum Actuator with Valve in Exhaust Pipe	
	Fuel Tank (l)	100	
Wheels & Tyres	Disc Type	Pressed Steel Disc Type with 6 Studs	
	Wheel Size	17.5 x 6.00 -127	
	Tyre Size (Front & Rear)	215 / 75R17.5	
	Spare Wheel	1 Spare Wheel with Carrier Mounted at Rear Chassis Frame	
Electrical	Electrical Output Current (v)	24	
	Battery	80D26L x 2	
	Alternator (Amp)	90	
Cabin	Cabin Features	Aerodynamic Designed, Mechanical Tilting, UN ECE R29 Cab Strength Compliance	
	Seating capacity	3	
Weight	Curb Weight (kg)	2,620	2,835
	Front Axle Weight (kg)	1,755	1,835
	Rear Axle Weight (kg)	865	1,000
Dimension	Wheelbase (mm)	3,815	
	Overall Length x Overall Width x Overall Height (mm)	6,635 x 2,115 x 2,280	
	Axle Tread [Front / Rear] (mm)	1,680 / 1,650	
	Overhang [Front / Rear] (mm)	1,110 / 1,710	
	Ground Clearance (Rear Axle) (mm)	185	205
Safety	Supplement Restraint System (SRS) Airbag for Driver	Standard	
	Anti-slip Regulator (ASR) with On/Off Function	Standard	
	Cab Tilt Warning	Standard	
	Reverse Alarm	Standard	
Accessories	Remote Keyless Entry, Immobilizer & Security Alarm system	Standard	
	Radio system with speakers	Standard	
	Door visors	Standard	
	Reverse sensors	Standard	



TAN CHONG INDUSTRIAL EQUIPMENT SDN BHD 197201001644 (13285-X)

A subsidiary of Tan Chong Motor Holdings Berhad 197201001333 (12969-P)

Lot 3, Jalan Perusahaan Satu, 68100 Batu Caves, Selangor Darul Ehsan, Malaysia.

Tel: 03-6189 9832 Fax: 03-6189 9336 Website: www.tcie.com.my

Note:

- (1) All images are for illustration purposes only. As product improvements may be introduced at any time, the specifications and other information in this brochure are subject to change without prior notice.
- (2) Performance is based on theoretical calculations. Actual performance depends on various parameters like actual load, road conditions, driver, condition of vehicles, etc.
- (3) Weights and dimensions mentioned are estimated and indicative only, actual may vary on selection of optional items.
- (4) Optional wheelbase is available.